

RUNner⁺



For sliding gates up to 12 m travel length and 800 kg weight



ACCU READY



< 0,5 W STANDBY

3560V000

Safety

- High safety due to fully automatic force memory
- Automatic detection of safety edges (8,2 kOhm or OSE) and light barriers (2 and 4 wire)
- Pre-warning function and dead-man operation
- Frequency-modulated safe SOMMER Radio Control System
- The use of active safety edges at the main and lateral edges are mandatory

Easy to install

- Left or right door operation adjustable via selection switch; no rewiring of motor and end switch is necessary
- Automatic / semi automatic closing is possible from the end position and partial-opening position; partial opening position is adjustable



Flexibility

- Energy-saving toroidal core transformer is environmentally-friendly and saves money
- Connection option for battery pack¹⁾ provides buffer in the event of a power failure

TECHNICAL DATA

| | |
|-------------------|------------------|
| Temperature range | -30 °C to +50 °C |
| Nominal voltage | AC 220 – 240 V |
| Torque | max. 28 Nm |
| Nominal frequency | 50/60 Hz |
| IP code | IP54 |

RUNner⁺ single operator

3560V000

incl. 1 x sliding gate operator, control unit STB-1, integrated radio receiver (FM 868.8 MHz)

¹⁾ available as accessory.

Last updated: 04/2016. Literal errors, errors and technical changes excepted.



SOMMER ANTRIEBS- UND FUNKTECHNIK GMBH | HANS-BÖCKLER-STR. 21-27 | D-73230 KIRCHHEIM/TECK
PHONE +49 (0)7021/8001-0 | FAX +49 (0)7021/8001-100 | INFO@SOMMER.EU | WWW.SOMMER.EU



SOMMERGMBH



SOMMER_GMBH