Pearl Status



3-command transmitter



Advantages:

- Bi-directional SOMlog2 radio system
- Downward compatible with the Somloq Rollingcode radio system, making it possible to control existing operators and radio receivers
- Efficient vibration motor for long battery life



Advantages of SOMloq2:

- Option of querying door position/ receiver status using the special red button without travel motion
- Maximum protection from hackers with 128 bit AES encryption with Rollingcode
- The option of querying door positions/reception status
- sensible vibrating feedback
- Auto-repeat function for comfortable opening while approaching the
- Improved range and higher reliability due to the hop function, since the signal is actively forwarded by SOMlog2 receivers

TECHNICAL DATA	
Radio system	SOMloq2
Radio commands	3
Frequency	FM 868.8 MHz FM 868.95 MHz
Range 1)	approx. 60–150 m
Dimensions	79×26×13 mm









Disturbance-resistant radio signal 28-bit AES encryption Collision resistance Bi-directional radio control system



1) Depending on surroundings. Last updated: 08/2017. Literal errors, errors and technical changes excepted.



SOMMER ANTRIEBS- UND FUNKTECHNIK GMBH | HANS-BÖCKLER-STR. 21-27 | D-73230 KIRCHHEIM/TECK PHONE +49 70 21 80 01-0 | FAX +49 70 21 80 01-100 | INFO@SOMMER.EU | WWW.SOMMER.EU



